



TECHNICAL DATA SHEET

THYSIS SCVF RAISED COWL SLATE VENTILATORS

SCVF 10-1 Slate Raised Cowl Ventilator (600 x 300mm)

SCVF 10-2 Slate Raised Cowl Ventilator (500 x 250mm)

SCVF 10-3 Slate Raised Cowl Ventilator (500 x 300mm)

SCVF 20-1 Slate Raised Cowl Ventilator (600 x 300mm)

Description:

The 10k and 20k cowl type range offer unobtrusive designs, have patented 'anti-splash sleeve' devices and flyscreen protection. 10k square to round adapters and flexible pipe for natural ventilation or mechanical extract and 20 square to round for 'passive stack' if required. Ventilation and is suitable for pitches of 15° and above.

Features:

- Moulded in 'High Impact Polystyrene'.
- UV Acrylic paint to match most slate colours and finishes.
- Suitable for use with pitches of 15° and above.
- Recommended 4mm flyscreen protection.
- Comply fully with the requirements of NHBC, BS 5250:2002 and BR Document C.
- 10k ventilation area 10,000mm².
- 20k ventilation area 20,000mm².

- **Spacing centres required to achieve a ventilation area of:**
- SCVF 10-1 5mm Continuous Opening – Install at 2.0m centres.
- SCVF 10-1 10mm Continuous Opening – Install at 1.0m centres.
- SCVF 20-1 5mm Continuous Opening – Install at 4.0m centres.
- SCVF 20-1 10mm Continuous Opening – Install at 2.0m centres.

STR110: Square to round pipe adapter to suit 112mm flexi-pipe